

TYRES

Product group	Tyres
Item number	10165650
Valid tyre size	155 R 12 C
LI / SI / PR	88 / 86 Q, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-05



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Onyx NY-05 is a tyre for light trucks and transporters.
- Its zigzag-shaped tread grooves and sipes provide very good grip on dry and wet roads.
- The reinforced rubber compound with 2 steel belts guarantees a long service life, high load capacities and good puncture resistance.

Technical Informations

Item number	10165650
EAN	6953913186368
Valid tyre size	155 R 12 C
LI / SI / PR	88 / 86 Q, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-05
M+S	M+S
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	6,06
Recommended rim size	4.50B
Permitted rim size	4.00B, 4J, 4.50J, 5J
Maximum air pressure [bar].	4,50
Section width (mm)	157
Outer diameter of tyre [mm].	550
Stat. radius (SLR) [mm]	250
Rolling circumference [mm].	1667
Tread depth (mm)	7,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
88 Q	560	160	Single	4,50	
86 Q	530	160	Twin	4,50	