

TYRES

Product group	Tyres	
Item number	10165710	
Valid tyre size	195 R 14 C	
LI / SI / PR	106 / 104 R, 8 PR	
TL/TT	TL	
Brand	Onyx	
Tread pattern	NY-05	





Notes and features

- The Onyx NY-05 is a tyre for light trucks and transporters.
- Its zigzag-shaped tread grooves and sipes provide very good grip on dry and wet roads.
- The reinforced rubber compound with 2 steel belts guarantees a long service life, high load capacities and good puncture resistance.



Technical Informations

Item number	10165710
EAN	6953913186429
Valid tyre size	195 R 14 C
LI / SI / PR	106 / 104 R, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-05
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	11,06
Recommended rim size	5.50J
Permitted rim size	5J, 6J
Maximum air pressure [bar].	4,50
Section width (mm)	198
Outer diameter of tyre [mm].	666
Stat. radius (SLR) [mm]	302
Rolling circumference [mm].	2018
Tread depth (mm)	8,7
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 R	950	170	Single	4,50	
104 R	900	170	Twin	4,50	