

## TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 10165800        |
| Valid tyre size | 155 R 12 C      |
| LI / SI / PR    | 88 / 86 Q, 8 PR |
| TL/TT           | TL              |
| Brand           | Mirage          |
| Tread pattern   | MR-W600         |



Bohnenkamp  
■ ■ ● Moving Professionals

**MIRAGE**

## Technical Informations

|                    |                 |
|--------------------|-----------------|
| Item number        | 10165800        |
| EAN                | 6953913172088   |
| Valid tyre size    | 155 R 12 C      |
| LI / SI / PR       | 88 / 86 Q, 8 PR |
| TL/TT              | TL              |
| Brand              | Mirage          |
| Tread pattern      | MR-W600         |
| M+S                | M+S             |
| 3PMSF              | 3PMSF           |
| Rolling resistance | D               |
| Wet grip           | D               |

|                              |                      |
|------------------------------|----------------------|
| Rolling noise [db].          | 73                   |
| Rolling noise level          | B                    |
| Antistatic                   | No                   |
| Tyre colour                  | Black                |
| ECE regulation number        | ECE 117,ECE 54       |
| Nettogewicht [kg] (gültig)   | 6,30                 |
| Recommended rim size         | 4.50B                |
| Permitted rim size           | 4.00B, 4J, 4.50J, 5J |
| Maximum air pressure [bar].  | 4,50                 |
| Section width (mm)           | 157                  |
| Tread width (mm)             | 155                  |
| Outer diameter of tyre [mm]. | 550                  |
| Stat. radius (SLR) [mm]      | 250                  |
| Rolling circumference [mm].  | 1667                 |
| Tread depth (mm)             | 7,3                  |
| E-Ready                      | No                   |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 88 Q  | 560                | 160          | Single        | 4,50                     |              |
| 86 Q  | 530                | 160          | Twin          | 4,50                     |              |