

TYRES

Product group	Tyres	
Item number	10165800	
Valid tyre size	155 R 12 C	
LI / SI / PR	88 / 86 Q, 8 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR-W600	





Technical Informations

Item number	10165800
EAN	6953913172088
Valid tyre size	155 R 12 C
LI / SI / PR	88 / 86 Q, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	6,30
Recommended rim size	4.50B
Permitted rim size	4.00B, 4J, 4.50J, 5J
Maximum air pressure [bar].	4,50
Section width (mm)	157
Tread width (mm)	155
Outer diameter of tyre [mm].	550
Stat. radius (SLR) [mm]	250
Rolling circumference [mm].	1667
Tread depth (mm)	7,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
88 Q	560	160	Single	4,50	
86 Q	530	160	Twin	4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.