

TYRES

Product group	Tyres
Item number	10165804
Valid tyre size	165 R 13 C
LI / SI / PR	94 / 92 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600



Bohnenkamp
■ ■ ● Moving Professionals

MIRAGE

Technical Informations

Item number	10165804
EAN	6953913173429
Valid tyre size	165 R 13 C
LI / SI / PR	94 / 92 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	8,20
Recommended rim size	4.50B
Permitted rim size	4J, 5J
Maximum air pressure [bar].	4,50
Section width (mm)	167
Tread width (mm)	165
Outer diameter of tyre [mm].	596
Stat. radius (SLR) [mm]	271
Rolling circumference [mm].	1806
Tread depth (mm)	8,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 R	670	170		4,50	
92 R	630	170		4,50	