

TYRES

Product group	Tyres
Item number	10165808
Valid tyre size	175 R 14 C
LI / SI / PR	99 / 98 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600



Bohnenkamp
Moving Professionals

MIRAGE

Technical Informations

Item number	10165808
EAN	6953913173436
Valid tyre size	175 R 14 C
LI / SI / PR	99 / 98 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	9,00
Recommended rim size	5J
Permitted rim size	4.50J, 5.50J
Maximum air pressure [bar].	4,50
Section width (mm)	178
Tread width (mm)	175
Outer diameter of tyre [mm].	634
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1921
Tread depth (mm)	8,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
99 R	775	170	Single	4,50	
98 R	750	170	Twin	4,50	