

TYRES

Product group	Tyres
Item number	10165826
Valid tyre size	215 / 60 R 16 C
LI / SI / PR	108 / 106 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300





Technical Informations

Item number	10165826
EAN	6953913173832
Valid tyre size	215 / 60 R 16 C
LI / SI / PR	108 / 106 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	12,70
Recommended rim size	6.50J
Permitted rim size	6J, 7J
Maximum air pressure [bar].	4,75
Section width (mm)	221
Tread width (mm)	215
Outer diameter of tyre [mm].	664
Stat. radius (SLR) [mm]	306
Rolling circumference [mm].	2012
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
108 R	1000	170	Single	4,75	
106 R	950	170	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.