

TYRES

Product group	Tyres
Item number	10165834
Valid tyre size	225 / 65 R 16 C
LI / SI / PR	112 / 110 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300



Bohnenkamp
■ ■ ● Moving Professionals

MIRAGE

Technical Informations

Item number	10165834
EAN	6953913174747
Valid tyre size	225 / 65 R 16 C
LI / SI / PR	112 / 110 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	13,80
Recommended rim size	6.50J
Permitted rim size	6J, 7J
Maximum air pressure [bar].	4,75
Section width (mm)	228
Tread width (mm)	225
Outer diameter of tyre [mm].	698
Stat. radius (SLR) [mm]	320
Rolling circumference [mm].	2115
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 R	1120	170	Single	4,75	
110 R	1060	170	Twin	4,75	