

TYRES

Product group	Tyres
Item number	10165838
Valid tyre size	185 / 75 R 16 C
LI / SI / PR	104 / 102 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600





Technical Informations

Item number	10165838
EAN	6953913172095
Valid tyre size	185 / 75 R 16 C
LI / SI / PR	104 / 102 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	11,70
Recommended rim size	5J
Permitted rim size	5.50J, 6J
Maximum air pressure [bar].	4,75
Section width (mm)	184
Tread width (mm)	185
Outer diameter of tyre [mm].	684
Stat. radius (SLR) [mm]	314
Rolling circumference [mm].	2073
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 R	900	170	Single	4,75	
102 R	850	170	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.