

TYRES

Product group	Tyres
Item number	10165838
Valid tyre size	185 / 75 R 16 C
LI / SI / PR	104 / 102 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600



Bohnenkamp
■ ■ ● Moving Professionals

MIRAGE

Technical Informations

Item number	10165838
EAN	6953913172095
Valid tyre size	185 / 75 R 16 C
LI / SI / PR	104 / 102 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W600
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	11,70
Recommended rim size	5J
Permitted rim size	5.50J, 6J
Maximum air pressure [bar].	4,75
Section width (mm)	184
Tread width (mm)	185
Outer diameter of tyre [mm].	684
Stat. radius (SLR) [mm]	314
Rolling circumference [mm].	2073
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 R	900	170	Single	4,75	
102 R	850	170	Twin	4,75	