

TYRES

Product group	Tyres
Item number	10165840
Valid tyre size	195 / 75 R 16 C
LI / SI / PR	107 / 105 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300





Technical Informations

Item number	10165840
EAN	6953913172071
Valid tyre size	195 / 75 R 16 C
LI / SI / PR	107 / 105 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	12,30
Recommended rim size	5.50J
Permitted rim size	5J, 6J
Maximum air pressure [bar].	4,75
Section width (mm)	196
Tread width (mm)	195
Outer diameter of tyre [mm].	698
Stat. radius (SLR) [mm]	320
Rolling circumference [mm].	2115
Tread depth (mm)	8,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
107 R	975	170	Single	4,75	
105 R	925	170	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.