

TYRES

Product group	Tyres	
Item number	10165842	
Valid tyre size	215 / 75 R 16 C	
LI / SI / PR	116 / 114 R, 10 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR-W300	





Technical Informations

Item number	10165842
EAN	6953913173849
Valid tyre size	215 / 75 R 16 C
LI / SI / PR	116 / 114 R, 10 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	14,50
Recommended rim size	6J
Permitted rim size	5.50J, 6.50J, 7J
Maximum air pressure [bar].	5,25
Section width (mm)	216
Tread width (mm)	215
Outer diameter of tyre [mm].	728
Stat. radius (SLR) [mm]	332
Rolling circumference [mm].	2206
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 R	1250	170	Single	5,25	
114 R	1180	170	Twin	5,25	