

TYRES

Product group	Tyres
Item number	10165842
Valid tyre size	215 / 75 R 16 C
LI / SI / PR	116 / 114 R, 10 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300



Bohnenkamp
■ ■ ● Moving Professionals

MIRAGE

Technical Informations

Item number	10165842
EAN	6953913173849
Valid tyre size	215 / 75 R 16 C
LI / SI / PR	116 / 114 R, 10 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-W300
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	14,50
Recommended rim size	6J
Permitted rim size	5.50J, 6.50J, 7J
Maximum air pressure [bar].	5,25
Section width (mm)	216
Tread width (mm)	215
Outer diameter of tyre [mm].	728
Stat. radius (SLR) [mm]	332
Rolling circumference [mm].	2206
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 R	1250	170	Single	5,25	
114 R	1180	170	Twin	5,25	