

TYRES

Product group	Tyres
Item number	10165864
Valid tyre size	215 / 65 R 15 C
LI / SI / PR	104 / 102 T, 6 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-700 AS



Bohnenkamp
■ ■ ● Moving Professionals

MIRAGE

Technical Informations

Item number	10165864
EAN	6953913174068
Valid tyre size	215 / 65 R 15 C
LI / SI / PR	104 / 102 T, 6 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-700 AS
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	11,60
Recommended rim size	6.50J
Permitted rim size	6J, 7J
Maximum air pressure [bar].	3,75
Section width (mm)	221
Tread width (mm)	215
Outer diameter of tyre [mm].	661
Stat. radius (SLR) [mm]	302
Rolling circumference [mm].	2003
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 T	900	190	Single	3,75	
102 T	850	190	Twin	3,75	