Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	10165876	
Valid tyre size	205 / 65 R 16 C	
LI / SI / PR	107 / 105 T, 8 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR-700 AS	



MIRAGE

Technical Informations Item number 10165876 EAN 6953913172675 Valid tyre size 205 / 65 R 16 C LI / SI / PR 107 / 105 T, 8 PR TL/TT ΤL Brand Mirage **Tread pattern MR-700 AS** M+S M+S 3PMSF 3PMSF **Rolling resistance** D D Wet grip

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	12,30
Recommended rim size	6J
Permitted rim size	5.5J0, 6.50J
Maximum air pressure [bar].	4,75
Section width (mm)	209
Tread width (mm)	205
Outer diameter of tyre [mm].	672
Stat. radius (SLR) [mm]	309
Rolling circumference [mm].	2036
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
107 T	975	190	Single	4,75	
105 T	925	190	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.