

TYRES

| | |
|-----------------|--------------------|
| Product group | Tyres |
| Item number | 10165878 |
| Valid tyre size | 205 / 75 R 16 C |
| LI / SI / PR | 113 / 111 R, 10 PR |
| TL/TT | TL |
| Brand | Mirage |
| Tread pattern | MR-700 AS |



Bohnenkamp
■ ■ ● Moving Professionals

MIRAGE

Technical Informations

| | |
|--------------------|--------------------|
| Item number | 10165878 |
| EAN | 6953913174600 |
| Valid tyre size | 205 / 75 R 16 C |
| LI / SI / PR | 113 / 111 R, 10 PR |
| TL/TT | TL |
| Brand | Mirage |
| Tread pattern | MR-700 AS |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Rolling resistance | D |
| Wet grip | D |

| | |
|------------------------------|----------------|
| Rolling noise [db]. | 73 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 117,ECE 54 |
| Nettogewicht [kg] (gültig) | 13,50 |
| Recommended rim size | 5.50J |
| Permitted rim size | 6J, 6.50J |
| Maximum air pressure [bar]. | 5,25 |
| Section width (mm) | 203 |
| Tread width (mm) | 205 |
| Outer diameter of tyre [mm]. | 714 |
| Stat. radius (SLR) [mm] | 334 |
| Rolling circumference [mm]. | 2163 |
| Tread depth (mm) | 9,7 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 113 R | 1150 | 170 | Single | 5,25 | |
| 111 R | 1090 | 170 | Twin | 5,25 | |