

TYRES

Product group	Tyres
Item number	10165890
Valid tyre size	235 / 65 R 16 C
LI / SI / PR	115 / 113 T, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-700 AS





Technical Informations

Item number	10165890
EAN	6953913173085
Valid tyre size	235 / 65 R 16 C
LI / SI / PR	115 / 113 T, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR-700 AS
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	14,80
Recommended rim size	7J
Permitted rim size	6.50J, 7.50J
Maximum air pressure [bar].	4,75
Section width (mm)	240
Tread width (mm)	235
Outer diameter of tyre [mm].	712
Stat. radius (SLR) [mm]	325
Rolling circumference [mm].	2157
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 T	1215	190	Single	4,75	
113 T	1150	190	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.