Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	10165904
Valid tyre size	155 R 13 C
LI / SI / PR	90 / 88 Q, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR200



MIRAGE

Technical Informations				
Item number	10165904			
EAN	6953913172460			
Valid tyre size	155 R 13 C			
LI / SI / PR	90 / 88 Q, 8 PR			
TL/TT	ть			
Brand	Mirage			
Tread pattern	MR200			
M+S	M+S			
Rolling resistance	D			
Wet grip	C			
Rolling noise [db].	72			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	7,00
Recommended rim size	4.50B
Permitted rim size	4.00B, 4J 4.50J, 5.00B, 5J
Maximum air pressure [bar].	4,50
Section width (mm)	157
Tread width (mm)	155
Outer diameter of tyre [mm].	578
Stat. radius (SLR) [mm]	264
Rolling circumference [mm].	1751
Tread depth (mm)	7,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
90 Q	600	160	Single	4,50	
88 Q	560	160	Twin	4,50	