

TYRES

Product group	Tyres	
Item number	10165910	
Valid tyre size	175 R 14 C	
LI / SI / PR	99 / 98 R, 8 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR200	





Technical Informations

Item number	10165910
EAN	6953913172491
Valid tyre size	175 R 14 C
LI / SI / PR	99 / 98 R, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR200
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	8,90
Recommended rim size	53
Permitted rim size	4.50J, 5.50J
Maximum air pressure [bar].	4,50
Section width (mm)	178
Tread width (mm)	175
Outer diameter of tyre [mm].	634
Stat. radius (SLR) [mm]	289
Rolling circumference [mm].	1921
Tread depth (mm)	7,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
99 R	775	170	Single	4,50	
98 R	750	170	Twin	4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.