Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	10165912
Valid tyre size	175 / 65 R 14 C
LI / SI / PR	90 / 88 T, 6 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR200



MIRAGE

Technical Informations				
Item number	10165912			
EAN	6953913172507			
Valid tyre size	175 / 65 R 14 C			
LI / SI / PR	90 / 88 T, 6 PR			
TL/TT	TL			
Brand	Mirage			
Tread pattern	MR200			
M+S	M+S			
Rolling resistance	D			
Wet grip	C			
Rolling noise [db].	72			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Rolling noise level В Antistatic No Tyre colour Black ECE regulation number ECE 117,ECE 54 7,10 Nettogewicht [kg] (gültig) **Recommended rim size** 5J Permitted rim size 5.50J 3,75 Maximum air pressure [bar]. Section width (mm) 177 Outer diameter of tyre [mm]. 584 Stat. radius (SLR) [mm] 269 Rolling circumference [mm]. 1770 Tread depth (mm) 8,1 E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
90 T	600	190	Single	3,75	
88 T	560	190	Twin	3,75	