

TYRES

Product group	Tyres	
Item number	10165912	
Valid tyre size	175 / 65 R 14 C	
LI / SI / PR	90 / 88 T, 6 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR200	





Technical Informations

Item number	10165912
EAN	6953913172507
Valid tyre size	175 / 65 R 14 C
LI / SI / PR	90 / 88 T, 6 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR200
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	7,10
Recommended rim size	5J
Permitted rim size	5.50J
Maximum air pressure [bar].	3,75
Section width (mm)	177
Outer diameter of tyre [mm].	584
Stat. radius (SLR) [mm]	269
Rolling circumference [mm].	1770
Tread depth (mm)	8,1
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
90 T	600	190	Single	3,75	
88 T	560	190	Twin	3,75	