

TYRES

Product group	Tyres	
Item number	10165914	
Valid tyre size	205 / 65 R 15 C	
LI / SI / PR	102 / 100 T, 6 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR200	





Technical Informations

Item number	10165914
EAN	6953913172514
Valid tyre size	205 / 65 R 15 C
LI / SI / PR	102 / 100 T, 6 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR200
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	11,70
Recommended rim size	6J
Permitted rim size	5.50J, 6.50J
Maximum air pressure [bar].	3,75
Section width (mm)	209
Tread width (mm)	205
Outer diameter of tyre [mm].	647
Stat. radius (SLR) [mm]	297
Rolling circumference [mm].	1960
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 T	850	190	Single	3,75	
100 T	800	190	Twin	3,75	