

TYRES

Product group	Tyres	
Item number	10165922	
Valid tyre size	225 / 65 R 16 C	
LI / SI / PR	112 / 110 T, 8 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR200	





Technical Informations

Item number	10165922
EAN	6953913173887
Valid tyre size	225 / 65 R 16 C
LI / SI / PR	112 / 110 T, 8 PR
TL/TT	TL
Brand	Mirage
Tread pattern	MR200
M+S	M+S
Rolling resistance	D
Wet grip	С
Rolling noise [db].	72

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	13,80
Recommended rim size	6.50J
Permitted rim size	6J, 7J
Maximum air pressure [bar].	4,75
Section width (mm)	228
Tread width (mm)	225
Outer diameter of tyre [mm].	698
Stat. radius (SLR) [mm]	320
Rolling circumference [mm].	2115
Tread depth (mm)	9,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 T	1120	190	Single	4,75	
110 T	1060	190	Twin	4,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.