

## TYRES

|                 |                   |
|-----------------|-------------------|
| Product group   | Tyres             |
| Item number     | 10165922          |
| Valid tyre size | 225 / 65 R 16 C   |
| LI / SI / PR    | 112 / 110 T, 8 PR |
| TL/TT           | TL                |
| Brand           | Mirage            |
| Tread pattern   | MR200             |



Bohnenkamp  
■ ■ ● Moving Professionals

# MIRAGE

## Technical Informations

|                     |                   |
|---------------------|-------------------|
| Item number         | 10165922          |
| EAN                 | 6953913173887     |
| Valid tyre size     | 225 / 65 R 16 C   |
| LI / SI / PR        | 112 / 110 T, 8 PR |
| TL/TT               | TL                |
| Brand               | Mirage            |
| Tread pattern       | MR200             |
| M+S                 | M+S               |
| Rolling resistance  | D                 |
| Wet grip            | C                 |
| Rolling noise [db]. | 72                |

|                              |                |
|------------------------------|----------------|
| Rolling noise level          | B              |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 117,ECE 54 |
| Nettogewicht [kg] (gültig)   | 13,80          |
| Recommended rim size         | 6.50J          |
| Permitted rim size           | 6J, 7J         |
| Maximum air pressure [bar].  | 4,75           |
| Section width (mm)           | 228            |
| Tread width (mm)             | 225            |
| Outer diameter of tyre [mm]. | 698            |
| Stat. radius (SLR) [mm]      | 320            |
| Rolling circumference [mm].  | 2115           |
| Tread depth (mm)             | 9,7            |
| E-Ready                      | No             |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 112 T | 1120               | 190          | Single        | 4,75                     |              |
| 110 T | 1060               | 190          | Twin          | 4,75                     |              |