Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	10165944	
Valid tyre size	215 / 75 R 16 C	
LI / SI / PR	116 / 114 R, 10 PR	
TL/TT	TL	
Brand	Mirage	
Tread pattern	MR200	



MIRAGE

Technical Informations				
Item number	10165944			
EAN	6953913170947			
Valid tyre size	215 / 75 R 16 C			
LI / SI / PR	116 / 114 R, 10 PR			
TL/TT	TL			
Brand	Mirage			
Tread pattern	MR200			
M+S	M+S			
Rolling resistance	D			
Wet grip	C			
Rolling noise [db].	72			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

В **Rolling noise level** Antistatic No Tyre colour Black ECE regulation number ECE 117,ECE 54 14,80 Nettogewicht [kg] (gültig) **Recommended rim size** 6J Permitted rim size 5.50J, 6.50J, 7J Maximum air pressure [bar]. 5,25 Section width (mm) 216 Tread width (mm) 215 Outer diameter of tyre [mm]. 728 Stat. radius (SLR) [mm] 332 Rolling circumference [mm]. 2206 Tread depth (mm) 9,7 E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 R	1250	170	Single	5,25	
114 R	1180	170	Twin	5,25	