

TYRES

Product group	Tyres	
Item number	10366030	
Valid tyre size	13 R 22.5	
LI / SI / PR	154 / 151 L	
TL/TT	TL	
Brand	Cargopower	
Tread pattern	CGC 180	

Notes and features

- The CGC180 is a tyre for construction and mixed use (regional and local transport).
- Its wide tyre shoulder and hard-wearing rubber compound provide extremely high durability.
- The tyre can be used on all axles and provides excellent grip, even on loose terrain.



Technical Informations

Item number	10366030
EAN	4040658080852
Valid tyre size	13 R 22.5
LI / SI / PR	154 / 151 L
TL/TT	TL
Brand	Cargopower
Tread pattern	CGC 180
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	D
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	73,37
Maximum air pressure [bar].	8,30
Section width (mm)	320
Outer diameter of tyre [mm].	1124
Rolling circumference [mm].	3480
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120		8,30	
151 L	3450	120		8,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.