

TYRES

Product group	Tyres	
Item number	10366042	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	152 / 148 M	
TL/TT	TL	
Brand	Cargopower	
Tread pattern	CSM 191	

Notes and features

- The CSM191 is a steering axle tyre for mixed use in regional and long haul traffic.
- The tyre provides excellent handling on various road surfaces like country roads or motorways.
- The special tread pattern optimally drains water and enables safe driving, not only on dry but also on wet roads.



Technical Informations

Item number	10366042
EAN	4040658080876
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	152 / 148 M
TL/TT	TL
Brand	Cargopower
Tread pattern	CSM 191
Axle position truck	FA
Rolling resistance	E
Wet grip	С
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	59,56
Maximum air pressure [bar].	8,50
Section width (mm)	312
Outer diameter of tyre [mm].	1014
Rolling circumference [mm].	3480
Tread depth (mm)	14,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130		8,50	
148 M	3150	130		8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.