

TYRES

Product group	Tyres
Item number	10366087
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 151 L, 20 PR
TL/TT	TL
Brand	Cargopower
Tread pattern	CDC 162

Notes and features

- The CDC162 is a drive wheel tyre for demanding use on building sites.
- The extra deep and flexible block tread ensures a long service life.
- The strong rubber compound and hexagonal layout of the blocks provide even power transmission and make the tyre extremely durable.
- Its non-directional tread pattern facilitates mounting.
- The tyre has an M+S marking.

Technical Informations

Item number	10366087
EAN	4040658080951
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	156 / 151 L, 20 PR
TL/TT	TL
Brand	Cargopower
Tread pattern	CDC 162
M+S	M+S
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	74
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	67,09
Maximum air pressure [bar].	8,50
Section width (mm)	312
Outer diameter of tyre [mm].	1082
Rolling circumference [mm].	3480
Tread depth (mm)	21,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 L	4000	120	Single	8,50	
151 L	3450	120	Twin	8,50	