

TYRES

Product group	Tyres	
Item number	10436000	
Valid tyre size	445 / 65 R 22.5	
LI / SI / PR	169 F	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WGP 23	





Notes and features

- The WGP 23 was specially developed for use on mobile cranes, small shovel loaders and Unimogs.
- The typical tread pattern provides excellent grip as well as very good self-cleaning properties and is suitable for various applications.
- Speed index F enables high speeds up to 80 km/h.



Technical Informations

Item number	10436000
EAN	4040658076787
Valid tyre size	445 / 65 R 22.5
Alternative size 1	18R22.5
LI / SI / PR	169 F
TL/TT	TL
Brand	Windpower
Tread pattern	WGP 23
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	106,75
Recommended rim size	14.00
Permitted rim size	13.00
Maximum air pressure [bar].	7,90
Section width (mm)	438
Outer diameter of tyre [mm].	1178
Stat. radius (SLR) [mm]	518
Rolling circumference [mm].	3478
Tread depth (mm)	30,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 F	5800	80		7,90	