

TYRES

Product group	Tyres	
Item number	10465305	
Valid tyre size	195 R 14 C	
LI / SI / PR	106 / 104 R	
TL/TT	TL	
Brand	Windpower	
Tread pattern	TransAce AL01	



Notes and features

- The Windpower TransACE AL01 is ideally suited for commercial delivery vehicles.
- It features a particularly robust, durable tread that is also suitable for extreme weather conditions.
- The two circumferential tread ribs ensure optimum cornering, even with fully loaded vehicles.
- The robust tread and optimum contact areas ensure good running characteristics, rapid steering response as well as even wear of the tyre.



Technical Informations

Item number	10465305
EAN	4040658075315
Valid tyre size	195 R 14 C
LI / SI / PR	106 / 104 R
TL/TT	TL
Brand	Windpower
Tread pattern	TransAce AL01
Rolling resistance	E
Wet grip	В
Rolling noise [db].	72
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	12,00
Maximum air pressure [bar].	4,50
Section width (mm)	198
Outer diameter of tyre [mm].	666
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 R	950	170		4,50	
104 R	900	170		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.