

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 10465345 |
| Valid tyre size | 225 / 70 R 15 C |
| LI / SI / PR | 112 / 110 R |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | TransAce AL01 |



Notes and features

- The Windpower TransACE AL01 is ideally suited for commercial delivery vehicles.
- It features a particularly robust, durable tread that is also suitable for extreme weather conditions.
- The two circumferential tread ribs ensure optimum cornering, even with fully loaded vehicles.
- The robust tread and optimum contact areas ensure good running characteristics, rapid steering response as well as even wear of the tyre.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 10465345 |
| EAN | 4040658075346 |
| Valid tyre size | 225 / 70 R 15 C |
| LI / SI / PR | 112 / 110 R |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | TransAce AL01 |
| Rolling resistance | E |
| Wet grip | B |
| Rolling noise [db]. | 72 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 14,50 |
| Maximum air pressure [bar]. | 4,50 |
| Section width (mm) | 228 |
| Outer diameter of tyre [mm]. | 697 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 112 R | 1120 | 170 | | 4,50 | |
| 110 R | 1060 | 170 | | 4,50 | |