

## TYRES

Product group	Tyres
Item number	10466387
Valid tyre size	8.25 R 16
LI / SI / PR	126 / 122 L, 14 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WGC 08



**WINDPOWER**  
Get Your Job Done

## Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

**Technical Informations**

<b>Item number</b>	10466387
<b>EAN</b>	4040658089794
<b>Valid tyre size</b>	8.25 R 16
<b>LI / SI / PR</b>	126 / 122 L, 14 PR
<b>TL/TT</b>	TT
<b>SET</b>	Tube + Flap
<b>Valve designation</b>	TR 175 A
<b>Brand</b>	Windpower
<b>Tread pattern</b>	WGC 08
<b>M+S</b>	M+S
<b>3PMSF</b>	3PMSF
<b>Axle position truck</b>	FA/RA/TR
<b>Rolling resistance</b>	D
<b>Wet grip</b>	C
<b>Rolling noise [db].</b>	72
<b>Rolling noise level</b>	B
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 54,ECE 117
<b>Nettogewicht [kg] (gültig)</b>	41,20
<b>Recommended rim size</b>	6.50H
<b>Permitted rim size</b>	6.00G, 6.50
<b>Maximum air pressure [bar].</b>	6,70
<b>Section width (mm)</b>	228
<b>Outer diameter of tyre [mm].</b>	850
<b>Stat. radius (SLR) [mm]</b>	454

---

Rolling circumference [mm].	2593
Tread depth (mm)	13,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 L	1700	120	Single	6,70	
122 L	1500	120	Twin	6,70	