

## TYRES

Product group	Tyres
Item number	10466391
Valid tyre size	8.25 R 15
LI / SI / PR	143 / 141 G (141 / 140 J), 18 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WSR 36



Bohnenkamp  
■ ■ ● Moving Professionals

**WINDPOWER**  
*Get Your Job Done*

## Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

## Technical Informations

Item number	10466391
EAN	4040658081323
Valid tyre size	8.25 R 15
LI / SI / PR	143 / 141 G (141 / 140 J), 18 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 444
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
Axle position truck	FA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	36,70
Recommended rim size	6.50
Permitted rim size	6.00, 7.00
Maximum air pressure [bar].	8,50
Section width (mm)	238
Outer diameter of tyre [mm].	832
Stat. radius (SLR) [mm]	386
Rolling circumference [mm].	2538

---

Tread depth (mm)	13,0
E-Ready	No

---

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 G	2725	90	Single	8,50	
141 J	2575	100	Single	8,50	
141 G	2575	90	Twin	8,50	
140 J	2500	100	Twin	8,50	