

TYRES

Product group	Tyres
Item number	10466394
Valid tyre size	8.25 R 16
LI / SI / PR	126 / 122 L, 14 PR
TL/TT	TT
SET	Tube + Flap
Brand	Windpower
Tread pattern	WGC 08



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10466394
EAN	4040658061813
Valid tyre size	8.25 R 16
LI / SI / PR	126 / 122 L, 14 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 175 A
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	C
Rolling noise [db].	71
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	41,20
Recommended rim size	6.50H
Maximum air pressure [bar].	6,70
Section width (mm)	234
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	397
Rolling circumference [mm].	2593
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
126 L	1700	120	Single	6,70	
122 L	1500	120	Twin	6,70	