

TYRES

Product group	Tyres
Item number	10466396
Valid tyre size	7.50 R 16
LI / SI / PR	122 / 118 L, 14 PR
TL/TT	TT
Brand	Windpower
Tread pattern	WGC 08



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10466396
EAN	4040658060922
Valid tyre size	7.50 R 16
LI / SI / PR	122 / 118 L, 14 PR
TL/TT	TT
Valve designation	TR 77 A
Brand	Windpower
Tread pattern	WGC 08
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	C
Rolling noise [db].	71
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	33,20
Maximum air pressure [bar].	7,70
Section width (mm)	216
Outer diameter of tyre [mm].	803
Stat. radius (SLR) [mm]	375
Rolling circumference [mm].	2449
Tread depth (mm)	12,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 L	1500	120		7,70	
118 L	1320	120		7,70	
118 L	1320	120			