

TYRES

Product group	Tyres	
Item number	10466405	
Valid tyre size	215 / 75 R 17.5	
LI / SI / PR	127 / 124 M, 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 24	





Notes and features

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.



Technical Informations

Item number	10466405
EAN	4040658059025
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	127 / 124 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24
M+S	M+S
Axle position truck	FA
Rolling resistance	D
Wet grip	С
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	28,30
Recommended rim size	6.00
Permitted rim size	6.75, 5.25
Maximum air pressure [bar].	8,30
Section width (mm)	216
Outer diameter of tyre [mm].	765
Rolling circumference [mm].	23333
Tread depth (mm)	13,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 M	1750	130	Single	8,30	
124 M	1600	130	Twin	8,30	