

## **TYRES**

Product group	Tyres	
Item number	10466407	
Valid tyre size	225 / 75 R 17.5	
LI / SI / PR	129 / 127 M, 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 24	





## Notes and features

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.



## **Technical Informations**

Item number	10466407
EAN	4040658059049
Valid tyre size	225 / 75 R 17.5
LI / SI / PR	129 / 127 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24
M+S	M+S
Axle position truck	FA
Rolling resistance	D
Wet grip	С
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	30,20
Recommended rim size	6.75
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	223
Outer diameter of tyre [mm].	781
Rolling circumference [mm].	2382
Tread depth (mm)	15,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 M	1850	130	Single	8,30	
127 M	1750	130	Twin	8,30	