

TYRES

Product group	Tyres
Item number	10466409
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Technical Informations

Item number	10466409
EAN	4040658055676
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	29,40
Recommended rim size	6.00
Permitted rim size	5.25, 6.75
Maximum air pressure [bar].	8,30
Section width (mm)	218
Outer diameter of tyre [mm].	766
Stat. radius (SLR) [mm]	358
Rolling circumference [mm].	2336
Tread depth (mm)	15,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 J	2180	100	Single	8,30	
133 J	2060	100	Twin	8,30	