

TYRES

Product group	Tyres
Item number	10466415
Valid tyre size	235 / 75 R 17.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTL 31



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Modern, heavy-load trailer tyre for local, regional and long-haul transport.
- Increased mileage due to special rubber compound.
- Stone-repellent sipe in the tread base.

Technical Informations

Item number	10466415
EAN	4040658055362
Valid tyre size	235 / 75 R 17.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTL 31
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	29,90
Recommended rim size	6.75
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	242
Outer diameter of tyre [mm].	791
Stat. radius (SLR) [mm]	365
Rolling circumference [mm].	2413
Tread depth (mm)	13,0

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	8,30	
141 J	2575	100	Twin	8,30	