# Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10466428	
Valid tyre size	245 / 70 R 17.5	
LI / SI / PR	136 / 134 M, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDR 09	





#### Notes and features

- The Windpower WDR09 was developed for drive wheel tyres in regional traffic.
- Due to its wide contact area the tyre provides safety in nearly all weather conditions and a shorter braking distance.
- The tyre's special tread pattern enables even wear and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10466428
EAN	4040658055386
Valid tyre size	245 / 70 R 17.5
LI / SI / PR	136 / 134 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 09
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	F
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	34,80
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	250
Outer diameter of tyre [mm].	791
Stat. radius (SLR) [mm]	372
Rolling circumference [mm].	2413
Tread depth (mm)	16,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 M	2240	130	Single	9,00	
134 M	2120	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.