

TYRES

Product group	Tyres
Item number	10466429
Valid tyre size	245 / 70 R 17.5
LI / SI / PR	143 / 141 J (144 / 144 F), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Technical Informations

Item number	10466429
EAN	4040658055683
Valid tyre size	245 / 70 R 17.5
LI / SI / PR	143 / 141 J (144 / 144 F), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	35,50
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	252
Outer diameter of tyre [mm].	793
Stat. radius (SLR) [mm]	364
Rolling circumference [mm].	2419
Tread depth (mm)	16,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	9,00	
144 F	2800	80	Single	9,00	
141 J	2575	100	Twin	9,00	
144 F	2800	80	Twin	9,00	