

## **TYRES**

Product group	Tyres	
Item number	10466429	
Valid tyre size	245 / 70 R 17.5	
LI / SI / PR	143 / 141 J (144 / 144 F), 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern WGC 28		





## Notes and features

- Construction site tyre of the newest generation for drive axles
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.



## **Technical Informations**

Item number	10466429		
EAN	4040658055683		
Valid tyre size	245 / 70 R 17.5		
LI / SI / PR	143 / 141 J (144 / 144 F), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WGC 28		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA/RA/TR		
Rolling resistance	Е		
Wet grip	В		
Rolling noise [db].	74		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	gültig) 35,50		
Recommended rim size	7.50		
Permitted rim size	6.75		
Maximum air pressure [bar].	9,00		
Section width (mm)	252		
Outer diameter of tyre [mm].	793		
Stat. radius (SLR) [mm]	364		
Rolling circumference [mm].	2419		
Tread depth (mm)	16,5		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	9,00	
144 F	2800	80	Single	9,00	
141 J	2575	100	Twin	9,00	
144 F	2800	80	Twin	9,00	