

TYRES

Product group	Tyres	
Item number	10466436	
Valid tyre size	265 / 70 R 19.5	
LI / SI / PR	40 / 138 M, 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	HN 355	





Notes and features

- Drive tread pattern for individual local and mixed use.
- High degree of adhesion and traction with low operating costs.
- Increased resilience against penetration and impact damages.



Technical Informations

Item number	10466436
EAN	4040658000881
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	140 / 138 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	E
Wet grip	D
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	40,10
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	8,30
Section width (mm)	255
Outer diameter of tyre [mm].	874
Stat. radius (SLR) [mm]	402
Rolling circumference [mm].	2666
Tread depth (mm)	16,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130	Single	8,30	
138 M	2360	130	Twin	8,30	