

TYRES

Product group	Tyres	
Item number	10466444	
Valid tyre size	265 / 70 R 19.5	
LI / SI / PR	143 / 141 J, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WTR 69	





Notes and features

- Modern, multifunctional trailer tyre for local, regional and long-distance transport.
- Long-life compound, flexible tread pattern for a long service life.
- Reinforced, wide tyre shoulder.



Technical Informations

Item number	10466444
EAN	4040658059131
Valid tyre size	265 / 70 R 19.5
LI / SI / PR	143 / 141 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69
M+S	M+S
Axle position truck	TR
Rolling resistance	С
Wet grip	С
Rolling noise [db].	72
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	38,60
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	8,30
Section width (mm)	258
Outer diameter of tyre [mm].	864
Rolling circumference [mm].	2635
Tread depth (mm)	13,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 J	2725	100	Single	8,30	
141 J	2575	100	Twin	8,30	