

TYRES

Product group	Tyres	
Item number	10466446	
Valid tyre size	285 / 70 R 19.5	
LI / SI / PR	145 / 143 M (146 / 144 L), 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 36	





Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.



Technical Informations

Item number	10466446		
EAN	4040658059148		
Valid tyre size	285 / 70 R 19.5		
LI / SI / PR	145 / 143 M (146 / 144 L), 16 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WSR 36		
M+S	M+S		
Axle position truck	FA		
Rolling resistance	С		
Wet grip	С		
Rolling noise [db].	73		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	41,80		
Recommended rim size	8.25		
Maximum air pressure [bar].	8,30		
Section width (mm)	280		
Outer diameter of tyre [mm].	891		
Stat. radius (SLR) [mm]	408		
Rolling circumference [mm].	2718		
Tread depth (mm)	14,0		
E-Ready	No		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 M	2900	130	Single	8,30	
146 L	3000	120	Single	8,30	
143 M	2725	130	Twin	8,30	
144 L	2800	120	Twin	8,30	