

TYRES

Product group	Tyres	
Item number	10466449	
Valid tyre size	285 / 70 R 19.5	
LI / SI / PR	144 / 142 M (145 / 143 L), 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDR 09	





Notes and features

- The Windpower WDR09 was developed for drive wheel tyres in regional traffic.
- Due to its wide contact area the tyre provides safety in nearly all weather conditions and a shorter braking distance.
- The tyre's special tread pattern enables even wear and a long service life.



Technical Informations

Item number	10466449		
EAN	4040658060977		
Valid tyre size	285 / 70 R 19.5		
LI / SI / PR	144 / 142 M (145 / 143 L), 16 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WDR 09		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	RA		
Rolling resistance	D		
Wet grip	D		
Rolling noise [db].	74		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	42,50		
Recommended rim size	8.25		
Maximum air pressure [bar].	8,30		
Section width (mm)	276		
Outer diameter of tyre [mm].	896		
Stat. radius (SLR) [mm]	415		
Rolling circumference [mm].	2733		
Tread depth (mm)	17,0		
E-Ready	No		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 M	2800	130	Single	8,30	
145 L	2900	120	Single	8,30	
142 M	2650	130	Twin	8,30	
143 L	2725	120	Twin	8,30	