

TYRES

Product group	Tyres
Item number	10466453
Valid tyre size	245 / 70 R 19.5
LI / SI / PR	141 /140 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTL 32



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Modern, heavy-load trailer tyre for local, regional and long-haul transport.
- Its special rubber compound provides lower rolling resistance and increased mileage.
- Its wet grip has been improved, as has its water dispersion capabilities thanks to a stone-repellent sipe in the tread base.
- Reduced heat generation.

Technical Informations

Item number	10466453
EAN	4040658072673
Valid tyre size	245 / 70 R 19.5
LI / SI / PR	141 /140 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTL 32
Axle position truck	TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	70
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	35,70
Recommended rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	252
Outer diameter of tyre [mm].	839
Stat. radius (SLR) [mm]	387
Rolling circumference [mm].	2556
Tread depth (mm)	13,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 J	2575	100	Single	8,30	
140 J	2500	100	Twin	8,30	