

TYRES

| Product group | Tyres | |
|-----------------|--------------------|--|
| Item number | 10466454 | |
| Valid tyre size | 245 / 70 R 19.5 | |
| LI / SI / PR | 141 / 140 J, 18 PR | |
| TL/TT | TL | |
| Brand | Windpower | |
| Tread pattern | WTL 32 | |





Notes and features

- Modern, heavy-load trailer tyre for local, regional and long-haul transport.
- Its special rubber compound provides lower rolling resistance and increased mileage.
- Its wet grip has been improved, as has its water dispersion capabilities thanks to a stone-repellent sipe in the tread base.
- Reduced heat generation.



Technical Informations

| Item number | 10466454 |
|------------------------------|--------------------|
| EAN | 4040658087677 |
| Valid tyre size | 245 / 70 R 19.5 |
| LI / SI / PR | 141 / 140 J, 18 PR |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | WTL 32 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Rolling resistance | D |
| Wet grip | В |
| Rolling noise [db]. | 71 |
| Rolling noise level | A |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 35,70 |
| Recommended rim size | 7.50 |
| Permitted rim size | 6.75 |
| Maximum air pressure [bar]. | 8,30 |
| Section width (mm) | 253 |
| Outer diameter of tyre [mm]. | 839 |
| Stat. radius (SLR) [mm] | 433 |
| Rolling circumference [mm]. | 2559 |
| Tread depth (mm) | 13,5 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| E-Ready No |
|------------|
|------------|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 141 J | 2575 | 100 | Single | 8,30 | |
| 140 J | 2500 | 100 | Twin | 8,30 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.