

TYRES

| Product group | Tyres | |
|-----------------|--------------------|--|
| Item number | 10466456 | |
| Valid tyre size | 285 / 70 R 19.5 | |
| LI / SI / PR | 150 / 148 J, 18 PR | |
| TL/TT | TL | |
| Brand | Windpower | |
| Tread pattern | WTR 69 | |





Notes and features

- Modern, multifunctional trailer tyre for local, regional and long-distance transport.
- Long-life compound, flexible tread pattern for a long service life.
- Reinforced, wide tyre shoulder.



Technical Informations

| Item number | 10466456 |
|------------------------------|--------------------|
| EAN | 4040658087905 |
| Valid tyre size | 285 / 70 R 19.5 |
| LI / SI / PR | 150 / 148 J, 18 PR |
| TL/TT | TL |
| Brand | Windpower |
| Tread pattern | WTR 69 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Rolling resistance | D |
| Wet grip | С |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 41,80 |
| Recommended rim size | 8.25 |
| Permitted rim size | 7.50, 9.00 |
| Maximum air pressure [bar]. | 8,30 |
| Section width (mm) | 279 |
| Outer diameter of tyre [mm]. | 893 |
| Stat. radius (SLR) [mm] | 427 |
| Rolling circumference [mm]. | 2724 |
| Tread depth (mm) | 14,0 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





| E-Ready No |
|------------|
|------------|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 150 J | 3350 | 100 | Single | 8,30 | |
| 148 J | 3150 | 100 | Twin | 8,30 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.