

TYRES

Product group	Tyres
Item number	10466465
Valid tyre size	235 / 75 R 17.5
LI / SI / PR	132 / 129 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24



WINDPOWER
Get Your Job Done

Notes and features

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.

Technical Informations

Item number	10466465
EAN	4040658089831
Valid tyre size	235 / 75 R 17.5
LI / SI / PR	132 / 129 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	29,90
Recommended rim size	6.75
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	238
Outer diameter of tyre [mm].	794
Stat. radius (SLR) [mm]	361
Rolling circumference [mm].	2422
Tread depth (mm)	13,0

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 M	2000	130	Single	8,30	
129 M	1850	130	Twin	8,30	